Toast Slicer

The toast slicer is used for slicing toast bread semi automatic.

Dimension (cm)			Motor Power (kw)	Voltage (V)	Approximate Weight (kg)	Slicing Capacity (loaves/h)	Slicing Thickness (mm)
Length	Width	Height					
75	65	130	0.37	380	98	100-200	12

Extruder

The extruder is located at the head of the automatic tunnel oven that are designed to extrude consistent flow of dough to conveyor. Equipped with an inverter to adjust output of dough. The installed paddle can be divided dough into 1, 2, 3 rows.

Model	Dimension (cm)			Pipe Diameter (inch)	Motor Power (kw)		Voltage (V)	Approximate Weight (kg)
	Length	Width	Height		Equipped Inverter	Without Inverter		
Barbari extruder	86	55	173	3	1.5	2.2	220	150
Lavash extruder	70	58	153	2	1.5	2.2	220	130

Divider

Divider is used in continuos and non continuos bread baking lines to divide the dough into accurate sized pieces.

Dimension (cm)			Production capacity (kg / h)	Tank capacity (kg)	Motor Power (kw)	Voltage (V)	Approximate Weight (kg)
Length	Width	Height					
80	80	170	1800	60	0.75	220	152

Grinder

The grinder is specially designed to chop bread and grinding sugar.

Dimension (cm)			Tank capacity (kg)	Motor Power (kw)	Voltage (V)	Approximate Weight (kg)
Length	Width	Height				
70	44	145	50	1.1	220	65